



Product Data Sheet  
Typical Properties

Product:	DAF 20 GA SDPC
Item ID:	20SDPC##01 (## - Width)
Film:	PVC
Standard Embossing:	Super Double Polish
Weight:	20 oz/sq. yd.
Thickness:	0.020"
Standard Widths:	54", 61", 72"
Standard Color:	Super Clear
Flame Resistance:	California Fire Marshal (CFM) Title 19 – Registration # F-59301
UV Resistance:	1,000 Hours Accelerated (AATCC 169 with deviations according to CPAI 84 section 4.2.2.2)
Cold Crack Resistance:	-20°F (ASTM D-2136)
Mildew Resistance:	No Growth (AATCC 30, Aspergillus Niger)

\*\*\*Test results and technical data are typical results, and not minimum standards. The above statements are of opinion that we believe to be accurate and reliable; results are accurate to the best of our knowledge at the time of writing. DAF makes no guarantee of results and assumes no obligation or liability whatsoever in connection with this information. Material is built to meet listed specifications in laboratory settings, and reflects results in industry-accepted lab test environments. Field conditions may vary from test environment. Product should be tested for specific usage by customer. Any person using the above product should first satisfy himself that this product is suitable for his use and meets all required health and safety requirements.

Revised 4/23/2019 – JP/LS