

Gold Finish PET ROLLUP Banner Film

7 mil 100% polyester film offering Anti-Curl, Gray back and a Gold Print Surface for Roll-up Retractable Banner Stands and Displays.

Key Features & Benefits

- 100% Polyester film for Roll-up displays, Windows, POP, Tradeshows.
- Curl resistant dimensionally stable film. 36" widths.
- Gold Color front and White backside.
- Universally compatible: Use with Solvent, Eco, UV and Latex printers.

<u>Properties:</u> The product offers a Gold print surface resulting in high impact images and graphics. Great for High-End Retail, Events, Posters, Window displays. Product trims clean and even with straight edge and blade. No warping, buckling or stretching under normal conditions.

<u>Handling</u>: Avoid touching material on print face which can cause finger prints when printed. If required, additional drying or out-gassing of inks can be achieved by laying printed graphics on table face up end for a period of time.

Printing:

- For best results calibrate media feed and bi-directional printing before using. 720 dpi, 8 pass and a max ink load below 300% offers a good balance between quality, speed and drying.
- Be sure the Ink is dry when it reaches the take up reel. For high ink Saturation Prints Ink may not dry fully before take-up reel. An external dryer or heat lamps pointed toward film during printing will accelerate drying before reaching take-up reel or allow print time to air dry
- Solvent or Eco-solvent:
 - Rollup or Lt Weight Banner setting.
 - DO NOT leave printed graphics on take-up reel for extended period of time as printed graphics can bond/stick to back of material if not completely dry.
- Roland Versaworks Suggested settings: (note; different settings may produce better results)
 - "SV-GG: Hi Gloss PVC Gray Glue", Print Quality = Standard, Res = 720dpi
- HP Latex suggested settings:
 - Generic Polyester Film (PET Film)

<u>Post Printing</u>: If product is not completely dry lay print face up for a period of time. In rollup displays lamination is not required but if desired thin PSA or liquid laminates are recommended.

Applications: Interior Roll-up stands, transit shelters, way-finds and sign frames.

<u>Installation:</u> Trim to recommended size according to display unit. Note: most rollup stands require up to 6 inches of extra material at the bottom graphic. Clip hanger bar to top of graphic and attach bottom of graphic to the leader material extending out of display unit. While holding graphic pull tension pin and slowly lower graphic into stand.