



Speed Vinyl – 10 mil Promotional-Intermediate Floor and Wall graphic material. 250g Nylon Fabric Reinforced PVC Texture Vinyl offering Anti-Slip print surface with High Tac but Clean Removal adhesive.

Key Features & Benefits

- Product construction is designed for quick and easy production and install. No over lamination or additional protection required.
- Surface: matte textured pebble finish with special nylon reinforcement fabric.
- Slip Resistant, Passed UL 410 and ANSI_NFSI B101 Standards.
- Roll Put-up: 54"x82ft.
- Adhesive: solvent/acrylic High-Tac but with clean removability.
- Release liner 140gsm PE coated Silicon Paper.
- Final tack 48 hours.
- Compatibility: Use with Mild & Eco Solvent, UVC, GEL and Latex printers. (A pretest is always recommended.)

Properties: 10 mil PVC (Nylon Fabric reinforced) self-adhesive white vinyl with pebble embossing.

Applications: Finished Smooth Concrete, Tile, Wood, Laminate and other indoor and outdoor mostly smooth surfaces. Product construction is designed for fast installation onto clean & dry surfaces. Recommended install temperature is above 50 degrees F. Rounded corners or soft shaped graphics will be less prone to lifting. For uncommon or critical surfaces (including even surface low pile Carpets) for promotional purposes only, These REQUIRE a printed pretest to determine suitability because of the huge variability in surfaces, carpet threads/weaves and stain resist treatments. Not recommended for hard highly textured surfaces.

Installation: Make sure surface is clean and dry. With the adhesive exposed work product onto receiving surface with particular attention to low points. Use Rubber Roller, Felt squeegee or another appropriate applicator. Rounded corners will help avoid edge release. Avoid highly textured surfaces.

Longevity (normal conditions): Outdoor = 1week to 1month. Indoor = 3 months up to one year.

Handling: Avoid touching print surface or introducing dust and dirt on to print face. This can cause anomalies and artifacts when printed. Always store unused material wound tight in original packaging.

Printing: Suggested Media Setting Universal Self-Adhesive Vinyl. Make sure that ink is dry when it reaches the take-up reel. An external dryer, fan and or heat lamp will accelerate drying.