



DAF Walk-On 8mil PVC Matte Non-Slip Lamination Film

This soft monomeric calendared 8 mil PVC lamination film has a Unique Pebble finished Surface which is qualified as Anti slip to the ANSI_NFSI B101 standard. Use this product as a Protection (Scuff Resistant) Laminate on Printed Graphics for many Graphic applications but product is specifically designed for Pedestrian Traffic in Retail, POP, Events, Tradeshows, Museums etc. Provides excellent abrasion resistance as well as some minor UV Protection (ink dependent).

Key Features & Benefits:

- Anti-Slip Rating; Pass ANSI_NFSI B101
- Caliper; 200 Micron, 8mil
- Adhesive; Solvent Polyacrylate (permanent) transparent pressure sensitive
- Put-up; 54"x164'
- Liner; 140gsm single Sided PE coated
- Finish; Matte abrasion resistant textured
- Longevity estimates; Indoor 3-5 years. Outdoor 1-2 years (Vertical surfaces/Mid-country)
- Shelf Life; 1 year (stored up to 25°C and 50% relative humidity), in original packing.

Applications:

- Floor Graphics, Tradeshow graphics, POP displays, Mouse pads, Counter mats, and other signage applications where a scuff-resistant finish is desired.
- Combine with a DAF PRINT MEDIA to create a slip-resist graphic to use on finished mostly smooth floors such as vinyl laminate, composite, wood, concrete, tile and low pile carpet.
 - DAF Matched Component printable products:
 - Longer-term; Semi-Permanent Adhesive.
 - *DAF Escape 3.2 mil bubble free print vinyl*
 - Medium-term; Removable adhesive.
 - *DAF Imprint 4 mil PSA print vinyl.*
 - Short-term; Ultra removable adhesive.
 - *DAF EZ-Tack 6mil PSA print vinyl.*

Floor Installation:

Make sure surface is clean and dry. With the adhesive exposed, work product onto receiving surface with particular attention to edges and low points. Use soft roller, Felt squeegee or another appropriate applicator. Rounded corners or soft shapes will help avoid edge release. Avoid textured surfaces. Longevity is influenced by inks, application surface, installation quality and environment. For critical applications a suitability test is recommended.