



ROLLUP Banner Film

8mil 100% polyester film offering Anti-Curl, High Opacity and a Satin Print Surface for Roll-up Retractable Banner Stands and Tradeshow Displays.

Key Features & Benefits

- Most affordable 100% Polyester film for Roll-up display stands.
- Anti-curl dimensionally stable film.
- Higher opacity grey-back which blocks ambient light.
- Universally compatible: Use with **Solvent, Eco, UV and Latex printers.**

Properties: The product offers a satin print surface resulting in saturated color for images and graphics while holding fine details and type. Product trims clean and even with straight edge and blade. No warping, buckling or stretching under normal conditions.

Handling: Avoid touching material on print face which can cause finger prints when printed. If required, additional drying or out-gassing of inks can be achieved by laying printed graphics on table face up end for a period of time.

Printing:

- For best results calibrate media feed and bi-directional printing before using. 720 dpi, 8 pass and a max ink load around 300% offers a good balance between quality, speed and drying.
- Ink should be dry when it reaches the take up reel. An external dryer or heat lamps pointed toward film during printing will accelerate drying before reaching take-up reel.
- Solvent or Eco-solvent:
 - DO NOT leave printed graphics on take-up reel for extended periods of time as printed graphics can bond/stick to back of material if not completely dry.
- Roland Versaworks suggested settings:
 - “SV-GG: Hi Gloss PVC Gray Glue”, Print Quality = Standard, Res = 720dpi
- HP Latex printer Suggested settings:
 - Front Panel Printer Media choice: Solvent Paper.
 - RIP Profile choice: HP White Satin Poster Paper.

Post Printing: If product is not completely dry lay print face up for a period of time. In rollup displays lamination is not required but if desired thin PSA or liquid laminates are recommended. For pop-up tradeshow booths use heavy 8-10mil semi-rigid laminate.

Applications: Interior Roll-up stands, Pop-up displays, transit shelters, way finds and sign frames.

Installation: Trim to recommended size according to display unit. Note: most units require up to 6 inches of extra material at the bottom graphic. Clip hanger bar to top of graphic and apply bottom of graphic to the leader material extending out of display unit. While holding graphic pull tension pin and slowly lower graphic into stand.