



DAF SAFEGUARD OPTI-CLEAR **LAMINATING FILM**

DAF SAFEGUARD OPTI-CLEAR is an optically clear 1.5 mil cold lamination PET film. It is available with an optically clear pressure sensitive adhesive and a high clarity polyester face film. Apply this clear layer over DAF Illusion perforated window films, clear window graphics, and any other application where optical clarity is key to extend the life of your wide format graphics. **For protecting your high quality, brilliant graphics, DAF SAFEGUARD is the clear choice.** Each roll is suspended and individually boxed.

Product Specifications

Product : DAF SAFEGUARD OPTI-CLEAR

Application: Protect Wide Format Window Graphics

Construction: 1.5 mil cold lamination film
with PSA

Standard Widths: 54"

Finish: Gloss

Put-Up: 100 feet

Face Film: Optically Clear PET Film

Adhesive Color: Optically Clear

Outdoor Life: 1+ years

RSAFOCPETG-54100

420 Braen Avenue, Wyckoff, New Jersey 07481

Toll Free: (800) 228-9837
Phone: (201) 251-1222
Fax: (201) 251-1221
Email: info@dafproducts.com
WebSite: www.dafproducts.com



Safeguard Opti-Clear is an Optically Clear Polyester Cold Pressure Sensitive Adhesive (PSA) Laminating Film.

1.5 mil optically clear PET film HIGH clear adhesive, with a PET release liner. This product provides excellent abrasion & weather resistance as well as some UV resistance when applied over printed graphics, particularly Perforated Window Films, as well as other substrates that require high optical clarity.

Key Features & Benefits:

- * 36-micron Polyester (Shrinkage under 1% without printed ink).
- * Solvent Polyacrylic (permanent) transparent pressure sensitive adhesive.
- * Put-up, 54"x100'.
- * Liner: 25-micron clear PET film.
- * Finishes available – Gloss.
- * Shelf Life: 1 year (stored up to 25°C and 50% relative humidity) in original packing.
- * Laminate reduces application time by making printed perforated window films easier to handle, install and remove.

Applications:

- * Use as a protective laminate where optical clarity is required such as Perforated Window Film and other graphics that require a highly clear laminate.

Installation:

- * It is best practice to NOT apply too much pressure during window application, which can cause the laminate to contact glass through the perforated holes. Further, it is always best to back tape edges on all perforated window graphics to prevent water and dirt from penetrating the edges.