

## DAF Ultra Clear Decal Window Film

### Key Features & Benefits

- Ideal for Window Décor, Window Advertising Graphics and other Glass Applications.
- Premium quality printable clear PVC film offers “optical type” clarity.
- Super smooth polyester liner gives “crystal” clear quality before/after application.
- Repositionable and Removable for up to 6 months.
- Solvent acrylic adhesive ensures long terms application.
- Print Mirror image for Second surface applications.
- White Ink background option will enhance the impact of printed graphics.
- Roll Put-up: 54” & 60” x 150 ft.

| PARAMETER            |                                    | VALUE                           |
|----------------------|------------------------------------|---------------------------------|
| Film                 | TYPE                               | 100um Optical clear PVC films   |
|                      | Opacity                            | 3%                              |
|                      | Finish                             | GLOSS (95@60°)                  |
|                      | E value (% at break)               | 220%/230% (MD/CD)               |
|                      | Shrinkage                          | 3%/0.5% (MD/CD)                 |
| Glue                 | Materials                          | 25um solvent based acrylic glue |
|                      | Type                               | Clear soft removable            |
|                      | Init tack (20min peel)/(N/in)      | 4N                              |
|                      | Hold: 9.8N/in <sup>2</sup> (Hours) | 72Hours                         |
|                      | 180 Peel (N/in)                    | 5N                              |
| Liner                | Thickness                          | 125um                           |
|                      | Type                               | clear matte PET                 |
| Shelf time           |                                    | 24 Months                       |
| Applying temperature |                                    | -5°C- 50°C                      |
| Outdoor durability   |                                    | 24Months                        |

### PRINTING INK

| Solvent | Eco-Sol | Aqueous Dye | Aqueous Pigment | UV | Latex |
|---------|---------|-------------|-----------------|----|-------|
|         | Y       |             |                 | Y  | Y     |

### APPLICATION

| Billboard Graphic | Rigid Board Graphic | Window Graphic | Wall Graphic | Floor Graphic | Vehicle Graphic | Signs |
|-------------------|---------------------|----------------|--------------|---------------|-----------------|-------|
|                   |                     | Y              |              |               |                 | Y     |